

UniFi[®] SWITCH



UniFi Switch Lite 16 PoE

The USW-Lite-16-PoE is a configurable Gigabit Layer 2 switch with sixteen Gigabit Ethernet ports for your RJ45 Ethernet devices. Eight ports also offer auto-sensing 802.3at PoE+ that provide up to a total PoE wattage of 45W for UniFi Access Points or other PoE devices. Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-16-PoE offers basic Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.



Mechanical

Dimensions	191.7 x 185 x 43.7 mm (7.55 x 7.28 x 1.72")
Weight	1.2 kg (2.65 lb)

Hardware

Total Non-Blocking Line Rate	16 Gbps
Max. Power Consumption	15W
Power Method	Universal AC Input: 100-240VAC
Power Supply	Internal 60W AC/DC Power Supply
Networking Interfaces	(16) 10/100/1000 Mbps Ethernet RJ45
PoE Interfaces	(8) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Management Interface	Ethernet In-Band
Max PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC

LEDs

System	(1) Power, Blue/White Flashing White: Bootup in Progress Flashing Blue: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at

